

TRANSFORMER DATA SHEET

DATE : 10/27/2008  
 CUSTOMER : HVES  
 CIRCUIT/LOCATION : HVES 53  
 MANUFACTURER : Square D  
 TRANSFORMER TYPE : Dry CLASS : AA  
 S/N :  
 THREE PHASE  SINGLE PHASE  : 60 HERTZ

VOLTAGE RATING: 480Y/277 - 208 Delta LV WINDING: ALUMINUM  
 KVA RATING: 112.5 Continuous, Self Cooled HV WINDING: ALUMINUM  
 Continuous, Forced Air LV: 150°C rise, BIL: 10 kV  
 HV: 150°C rise, BIL: 10 kV

NAMEPLATE DATA

Core & Coils	
Case & Fittings	
Oil in Gallons	
Weight in Pounds	1000

Impedance volts : 4.6 % at rated volts at : 112.5 KVA

**TRANSFORMER TEST DATA**

MEGGER TEST RESULTS

1 Minute

High-> Ground	<input type="text"/>	M-Ohms, @	<input type="text"/>	kV DC
Low -> Ground	<input type="text"/>	M-Ohms, @	<input type="text"/>	kV DC
High-> Low	<input type="text"/>	M-Ohms, @	<input type="text"/>	kV DC

POLARIZATION  
INDEX


CAPACITANCE in  
MICRO-FARAD


TRANSFORMER TTR TESTS

TAP (V)	CALC. TTR	PHASE 1	PHASE 2	PHASE 3

COMMENTS

Tag 11178  
 Date of manufacture: n/a  
 Stored at n/a